

- Available up to G+31, Auto door With integrated ARD.
- All floor displays and car push switches through 2 wire interface.
- only 1magnet per floor and 1 door zone on car top for any number of floors.
- Auto learning for slowing detection and easy commissioning.
- Encoder signal for floor sensing.
- Detailed diagnosis of individual components ensures safety and reliable operation.
- Runs with minimum feature even failure of door zone and ESR switches.
- Inbuilt stabilizer designed to run the elevator from 180volt to 270volts and prevent RCR, Brake over heating.
- Attached with panel guard to protect the system from phase loop and voltage fluctuations with complete 3 phase voltage display.
- Intelligent algorithm to attend any calls within 10 seconds for standard configuration.
- VIP option, fire man switch, overlode detection & protection and all other standard interface integrated Gong bell integrated with annunciator.
- User selectable floors, software functional options, delay times and important configurations.
- PC interface error diagnosis report, elevator error history & service details available.
- Maintenance work is very efficient in short time.
- Dedicated power supply board enhances the reliability of product.
- Regulated 24 volt 4 channel DC output for field and internal wiring.
- Over load, Short circuit protected outputs with error indicator.



Mabara Manufacturing Company
 8/100, Thiruvalluvarpuram, 1st Street,
 Choolaimedu, Chennai - 600 094
 Tamilnadu, India
 Tel : +91 - 44 - 2374 3643
 Mobile : +91 - 93400 50607
 Email : contact@mabara.com